



HELICOPTERS

H155

Technical Data

2017



AIRBUS

3 Baseline Aircraft Definition

GENERAL

- Fuselage comprising cabin and baggage hold
- Baggage hold with floor tie-down net (LH and RH side)
- Tail boom with stabilizer fitted with 2 lateral fins and a shrouded tail rotor built into the vertical fin
- Retractable tricycle landing gear with axially lockable castering nose wheel unit, assisted differential brakes on pilot's and copilot's stations and parking brake
- 3 heated pitot heads
- 6 built-in foot-steps (3 on each side) for access to transmission deck
- Anti-corrosion protection
- Structural reinforcements for 1,600 kg (3,527 lb) cargo-sling
- Structural reinforcements for external hoist
- Jacking, hoisting, mooring and gripping points
- Interior colour: light grey
- Exterior colour:
 - the fuselage is painted as per standard colour chart (scheme and colours, gloss or matt polyurethane finish, white + 2 colours), unless modified by option
 - the landing gears are light blue
 - the transmission deck (MGB & tail rotor drive shaft) are white
 - the main rotor and tail rotor cover are grey
 - the main rotor blades are kaki and the tail rotor blades are black

COCKPIT / CABIN

- 1 multipurpose cabin
- 2 removable pilot and copilot energy attenuating high back-rest seats, adjustable in reach and height, each fitted with a 5 points harness
- 1 glass windshield
- 2 hinged pilot and copilot doors, jettisonable with tinted windows, allowing access to cockpit and front passenger row, each fitted with a sliding window
- 2 jettisonable tinted windows located between cockpit and cabin doors
- 2 passenger sliding doors with jettisonable tinted windows
- 2 externally mounted cockpit and cabin footsteps on each side
- 2 tinted upper panes
- Cabin upholstery
- Dual flight controls
- Fuel shut-off controls
- 1 rotor brake control
- 1 heating / demisting / ventilation system
- 2 windshield wipers
- 1 portable fire-extinguisher in cockpit
- 2 illuminated chart holders
- 2 headset hooks
- Stowage place in the doors for flight documents
- 1 flight manual

INSTRUMENTS

- 2 Primary Flight Displays (PFD)
- 2 Navigation Displays (ND)
- 1 dual screen Vehicle and Engine Management Display (VEMD®) providing the following information:
 - First Limitation Indicator (FLI): limitation related to the first power limitation: NG, T4, TRQ
 - Engine oil temperature/pressure indicator
 - Hydraulic pressure
 - Ammeter and voltmeter
 - OAT
 - Enhanced usage monitoring functions
 - ◆ Engine cycle counting
 - ◆ Automatic engine check
- 1 Caution Advisory Display (CAD) providing the following information:
 - Caution advisory display (amber, green and blue messages)
 - Fuel quantity
 - Fuel pressure
 - ΔNG (back-up mode)
- 2 Instrument Control Panels (ICP)
- 1 mission display 10.4"
- 1 stand-by gyro-horizon
- 1 stand-by anemometer
- 1 stand-by altimeter
- 1 stand-by magnetic compass
- 1 stand alone DME indicator
- 1 landing gear position selector and indicator
- 2 stop watches
- 1 triple tachometer for rotor and engine 1 and 2 free turbine r.p.m.
- 1 tachometer for rotor on copilot's side
- 1 warning panel (red alarms)
- 2 master alarm lights
- 2 manoeuvre limit lights
- 2 "L/G not extended" warning lights
- 1 Automatic Pilot Mode Selector (APMS)
- 1 Reconfiguration Control Unit (RCU)
- 1 fuel circuit control and inspection panel
- 1 AHRS control box
- 1 overhead panel including an engine control panel, 2 dual fire extinguishing controls for engine bays, 1 dual fire extinguishing control for baggage hold and 1 electrical control panel
- 1 brake hydraulic circuit pressure gauge on pilot side floor
- 2 Attitude and Horizontal Reference Systems (AHRS)
- 2 Air Data Computers (ADC)
- 1 radar altimeter (radar altitude displayed on NDs)
- 1 nose mounted rack with the following avionics modules:
 - 2 Flight Data Computer Modules (FDCM)
 - 1 Automatic Pilot Module (APM)
 - Spare for 1 Miscellaneous Flight Data Acquisition Unit (MFDAU++)

POWER PLANT

- 2 Turbomeca ARRIEL 2C2 turbine engines with dual channel Full Authority Digital Engine Control (FADEC) system, and fitted with 4 chip detectors cabled with 1 warning light on warning panel
- The Digital Engine Control Unit (FADEC) provides the following main functions:
 - Variable rotor speed governing
 - OEI training mode
 - Automatic starting sequence
- Each engine is equipped with an anti-icing fuel system (efficient down to O.A.T. = -20° C)
- Automatic (FADEC controlled) engine governing in back-up mode
- 1 fuel system including 6 tanks split into 2 groups, with a total usable capacity of 1,257 litres (332 US gal), 4 immersed canister booster pumps, 1 transfer pump and low level fuel indication
- 2 engine lubrication and oil cooling systems
- 1 fuzzi burner system on engine lubrication system
- 2 engine fire detection and extinguishing systems
- 2 engine anti-icing air-intake grids
- 2 phase angle torquemeter sensors
- Single side engine flushing port (without cowlings removal)
- Single side fuel filler with door

TRANSMISSION SYSTEM

- 1 main gearbox with oil level sight, magnetic plug, oil pressure and temperature sensors, 1 dual-pump lubrication system, thermal-switch, 2 rotor tachometer sensors, access ports for endoscope and oil sampling, and 2 chip detectors wired to the Caution Advisory Display
- 2 free wheels integrated to the main gearbox
- 1 main gearbox oil cooling system
- 2 engine / main gearbox coupling shafts
- 1 tail rotor drive shaft
- 1 rotor brake
- 1 tail gearbox with oil level sight and 1 chip detector wired to the Caution Advisory Display

ROTORS AND FLIGHT CONTROLS

- 1 main rotor with:
 - 5 glass / carbon-fibre blades
 - 1 SPHERIFLEX® rotor head fitted with lower gust and droop stops
 - 1 rotor mast fitted with rotor r.p.m. phonic-wheel
- 1 FENESTRON® type tail rotor with 10 composite material blades built into the vertical fin.
- 1 flight control system, fitted with 3 dual-chamber / dual-body main servo-units (on cyclic and collective pitch channels) and 1 dual-chamber / dual-body rear servo-unit (on tail rotor pitch control channel)
- 1 Dual Digital Automatic Flight Control System (4-axis type) including upper modes

ELECTRICAL INSTALLATION

- Power generation system:
 - 2 starter / generators (160 Amp, 28 V DC)
 - 43 Amp / hr nickel-cadmium battery with temperature sensor and warning light
 - 1 external 28 V DC power connector
 - 1 additional maintenance ICS jack in the ground power receptacle compartment
- Power distribution system:
 - 2 primary bus bars
 - 2 essential bus bars
 - 2 high load bus bars (80 A) – for optional equipment only
 - 1 battery bus
 - 2 breaker panels in radome
- 1 breaker panel in cockpit
- Lighting:
 - 1 double red and white tail fin anti-collision light
 - 1 LH side retractable landing light (450 W)
 - 1 RH side retractable swivel light (450 W)
 - 3 position lights (red, green, white)
 - adjustable instrument lighting
 - 2 utility lights in the cockpit
 - 1 instrument light for flight in stormy conditions
 - overhead lights in cabin and cargo compartment
- 2 x 28 V DC power outlets in cabin
- 1 emergency battery for automatic lighting of the cabin central overhead lights and call signs

HYDRAULIC GENERATION

- 2 independent hydraulic systems feeding the servo-units, landing gear actuation system and assisted brakes
- 1 self-sealing hydraulic ground coupling
- 1 stand-by hydraulic system with electro-pump for emergency activation of the landing gear and for hydraulic assistance on ground (engines not running)

AIRBORNE KIT 1

- 3 pitot head covers
- 2 static vent plugs
- 2 engine air-intake covers
- 2 engine exhaust pipe covers
- 7 mooring rings
- 2 rough weather tie-down rings
- 2 gripping rings
- 1 main blades tie-down kit
- 1 set of jacking pads
- 1 fuel tanks bleed tool
- 1 data case
- 1 airborne kit stowing bag

¹ Weight not included in standard aircraft empty weight.

AIRBUS

© AIRBUS HELICOPTERS, Aeroport International
Marseille Provence - 13725 Marignane Cedex -
France

2017 - All rights reserved
Airbus Helicopters' logo and the names of its
products and services are registered trademarks.
Airbus Helicopters reserves the right
to make configuration and data changes
at any time without notice. The facts and
figures contained in this document and
expressed in good faith do not constitute any
offer or contract with Airbus Helicopters.

Designed by AIRBUS HELICOPTERS
Photos: © AIRBUS HELICOPTERS
Cover photo: © Patrick Penna - 2015
Printed by SPI (France)

155 B1 17.100.01 E